



UNIVERSAL MOUNTING CAPABILITY PROVIDES CONTROLLED ACCESS OF DOORS, CLOSETS AND CABINETS.

180/ 280 SERIES

SURFACE MOUNT BOLT LOCKS

Universal Mounting Capability Provides Controlled Access of Doors, Closets and Cabinets.

The IDC universal surface mount electric bolt locks are available in failsafe and failsecure. The addition of a card reader, digital keypad or remote control provides access control and convenience of use for a variety of applications.



Applications

The IDC 180 and 280 series locks provide the ability to electronically secure several door configurations.

- Swinging or sliding doors
- Outswing or inswing doors
- Closet doors
- Pharmaceutical cabinets
- Gun cabinets
- Utility cabinets
- Museum display cases
- Retail display cases

Models

- 180ALIV** Surface mount, left hand, failsafe, with auto relock
- 180ARIV** Surface mount, right hand, failsafe, with auto relock
- 180ALRIV** Top Jamb, left hand reverse, failsafe, with auto relock
- 180ARRIV** Top Jamb, right hand reverse, failsafe, with auto relock
- 280LHV** Surface mount, left hand, or top jamb mount right hand reverse, failsecure less auto relock
- 280RHV** Surface mount, right hand, or top jamb mount, left hand reverse, failsecure less auto relock


Finish

- 628 Aluminum (*standard*)
- 335 Black


Options

- B** Bolt position sensor, SPDT
- D** Door position sensor, SPDT
- BR64XL** Rectifier for AC Operation

Installation



Surface Mount
Outswing Door



Top Jamb
Inswing or Sliding Door

Specifications

- Lock Dimensions** 6"L x 2"W x 2"H (152.4 x 50.8 x 50.8mm)
- Bolt** Solid Stainless Steel
0.625" dia. x 0.5" throw (15.9 x 12.7mm)
- Dual Voltage Coil** 0.9 Amp @ 12VDC Continuous
0.45 Amp @ 24VDC Continuous

International Door Closers, Inc.

COPYRIGHT 2014 INTERNATIONAL DOOR CLOSERS, INC

West: 800-544-4422 • East: 800-225-6737

www.intldoorclosers.com