



# 30-4 SERIES

## ELECTRIC STRIKE

### Features

The IDC 30-4 Series electric strike is designed for use with rim mount exit devices having pullman type latchbolts or the top pullman latch of a surface vertical-rod exit device.

- All stainless steel for corrosion resistance and strength
- Tamper resistant, heavy-duty construction
- Set screws for adjustment lockdown
- Milled ramps to better accommodate deadlatches
- Integrated shim for quick customization of faceplate thickness (3/4" to 1/2")
- In-frame horizontal adjustability
- Pullman keeper
- Non-handed, reversible
- Failsecure (standard) Failsafe (optional)
- 3/4" keeper depth
- Static strength 1,500 lbs.
- Dynamic strength 70 ft-lbs.

### Model

**30-4** Electric Strike with 0.75" (19mm) faceplate. Except .5" (12.7mm) without 1/4" spacer.

### Specifications

**12** 0.51 Amp @ 12VDC, 24 OHMS  
**24** 0.25 Amp @ 24VDC, 96 OHMS

### Finish

- |                                |                            |
|--------------------------------|----------------------------|
| 630 Stainless Steel (standard) | 625 Bright Chrome          |
| 606 Dull Brass                 | 626 Dull Chrome            |
| 612 Dull Bronze                | 629 Bright Stainless Steel |
| 613 Oil Rubbed Bronze          |                            |

### Options

- |               |                            |
|---------------|----------------------------|
| <b>FS</b>     | Fail-safe operation        |
| <b>LBM-30</b> | Latchbolt Monitor          |
| <b>LCM-30</b> | Locking Cam Monitor        |
| <b>BR64XL</b> | Rectifier for AC operation |

### Listings

- UL 10C, 3 hour fire-rated (fail secure only)
- UL1034, burglary-resistant rated
- ANSI/BHMA A156.31, Grade 1
- CAN4-S104 (ULC-S104) fire door conformant
- DOD approved
- New York City accepted

