



30-4 SERIES

ELECTRIC STRIKE

Features

The IDC 30-4 Series electric strike is designed for use with rim mount exit devices having pullman type latchbolts or the top pullman latch of a surface vertical-rod exit device.

- All stainless steel for corrosion resistance and strength
- Tamper resistant, heavy-duty construction
- Set screws for adjustment lockdown
- Milled ramps to better accommodate deadlatches
- Integrated shim for quick customization of faceplate thickness (3/4" to 1/2")
- In-frame horizontal adjustability
- Pullman keeper
- Non-handed, reversible
- Failsecure (standard) Failsafe (optional)
- 3/4" keeper depth
- Static strength 1,500 lbs.
- Dynamic strength 70 ft-lbs.

Model

30-4 Electric Strike with 0.75" (19mm) faceplate. Except .5" (12.7mm) without 1/4" spacer.

Specifications

12 0.51 Amp @ 12VDC, 24 OHMS
24 0.25 Amp @ 24VDC, 96 OHMS

Finish

- | | |
|--------------------------------|----------------------------|
| 630 Stainless Steel (standard) | |
| 606 Dull Brass | 625 Bright Chrome |
| 612 Dull Bronze | 626 Dull Chrome |
| 613 Oil Rubbed Bronze | 629 Bright Stainless Steel |

Options

- | | |
|---------------|----------------------------|
| FS | Fail-safe operation |
| LBM-30 | Latchbolt Monitor |
| LCM-30 | Locking Cam Monitor |
| BR64XL | Rectifier for AC operation |

Listings

- UL 10C, 3 hour fire-rated (fail secure only)
- UL1034, burglary-resistant rated
- ANSI/BHMA A156.31, Grade 1
- CAN4-S104 (ULC-S104) fire door conformant
- DOD approved
- New York City accepted

