



JAMB BRACKETS

HARDWARE REINFORCEMENTS



FRAME REINFORCEMENTS

- Hollow metal frame reinforcements for most IDC concealed overhead holder/stop jamb brackets

R4401

- Frame reinforcement for 4000 series concealed holders/stops
- Holes pre-drilled and tapped 10-32
- 3/4" wide x 1/8" thick x 7" long, zinc plate CRS
- Part is non-handed but must be installed with stamped arrow toward butt jamb

R90541

- Frame reinforcement for 1000 and 1000SL concealed overhead holders/stops
- Holes pre-drilled and tapped 1/4-20
- 1" wide x 1/8" thick x 7" long, zinc plate CRS
- Part is non-handed but must be installed with stamped arrow toward butt jamb



R4401

R90541

ANGLE JAMB BRACKETS

- Used to change standard surface mounted overhead holders to flush transom or hinge side mounted. Attaches to standard jamb bracket.
- 44443 for 4400 & 3300A
- 70377 for 7000 flush transom only
- 90541 for 8000 (hold open or stop flush transom, stop only hinge side) and 9000
- Available in all BHMA finishes



ANGLE JAMB BRACKETS

- To drop surface mounted overhead holder/stops (i.e. to clear blade stops) or to fill jamb bracket mortise when removing a concealed holder/stop
- 7000JF for 7000
- 9000JF (1/4" thick) for 1000, 1000SL, 8000, 9000, 9000A
- 4000JF (3/16" thick) for 4000, 3300A, 4400
- Available in all BHMA finishes



International Door Closers, Inc.

COPYRIGHT 2017 INTERNATIONAL DOOR CLOSERS, INC

West: 800-544-4422 • East: 800-225-6737

www.intldoorclosers.com