



DISTRIBUTOR OF TUCKER
AUTO-MATION DOOR PRODUCTS



POWER PEDESTRIAN SWINGING DOORS SW19.10 & SW10.10



■ ALUMINUM END CAPS

FEATURES

ARCHITECTS AND BUILDING OWNERS ALL AGREE THEY NEED TO FIND WAYS TO :

- ELIMINATE
- FRIVOLOUS LAWSUITS
- GUARANTEE SUSTAINABILITY
- HIRE A DEPENDABLE NETWORK OF DOOR PROFESSIONALS
- UNCOVER HIDDEN COSTS
- GATHER MORE BUSINESS INTELLIGENCE LIKE STORE TRAFFIC OR BUILDING MAINTENANCE COST
- PROVIDE A SECURE AND MONITORED FACILITY
- COMPLY WITH THE LATEST BUILDING CODES UL / CUL, AND ACCESSIBILITY GUIDELINES MANDATED BY THE LAW

THEY REALIZE A DOOR IS NOT... "JUST A DOOR" BUT :

- A POINT OF ENTRY/EXIT
- A STRATEGIC AREA FULL OF PROMISING DATA
- AN AREA WHERE ALL TRAFFIC CONVERGES
- A SPACE WHERE YOU CAN CAPTURE ALL IMAGES

THE ALL IN ONE ENTRANCE SOLUTION

- NON-HANDED
- SELF-TUNING, SELF-LEARNING
- EXTREMELY SILENT
- COMPLIES WITH ANSI A156.19 & A156.10
- UL - CERTIFIED FOR USE AS FIRE DOOR OPERATORS (3 HOUR RATING)
- COMPLIES WITH ALL US AND CANADIAN ADA REQUIREMENTS

SW19.10

LOW ENERGY



- MIN 5 SEC FROM CLOSE TO OPEN
- STAY OPEN FOR 5 SEC
- FORCE: 15 lbs - 6.8 kg
- PUSH OR PULL (IN DOOR OUT SWING)
- ACTIVATION: KNOWING ACT
- SAFETY DEVICE: OPTIONAL

SW10.10

FULL ENERGY



- MIN 1.5 SEC FROM CLOSE TO OPEN
- STAY OPEN 1.5 SEC
- FORCE: 30 lbs - 13.6 kg
- PUSH OR PULL (ARM APPLICATION)
- ACTIVATION: MOTION DETECTOR OR KNOWING ACT
- SAFETY DEVICE: DOOR-MOUNTED SENSOR OR OVERHEAD PRESENCE SENSOR

International Door Closers, Inc.

COPYRIGHT 2017 INTERNATIONAL DOOR CLOSERS, INC

West: 800-544-4422 • East: 800-225-6737
www.intldoorclosers.com