



SERIES 1800

Series 1800

Features

- Factory tested to meet or exceed ANSI 156.4 Grade 1
- Barrier Free operation to comply with Federal Accessibility Standards (ADA) complying with ANSI 117.1
- Narrow design permits installation on most glass and aluminum doors without adapters
- Standard application for regular arm and Top Jamb installation; optional parallel arm installation (requires optional PA bracket.)
- Two Adjustment Valves: Closing and Latching speeds controlled by separate regulating valves, adjustable after installation. (Three valves with optional back-check)
- Ranges of Sizes
 - Standard: 1802, 1803, 1804, and 1805
 - Back-Check: 1802-BC, 1803-BC, 1804-BC, and 1805-BC
- Slim Plastic Cover or Full Cover (optional)
- 5 year warranty
- All Weather Fluid

Optional Features

- Slim or Full Plastic Cover
- Hold-Open Arm
- Drop Plates
- Sex Nuts and Bolts



Finishes

- AL - Aluminum
- DU - Storefront Bronze

Description	Dimensions
A. Length of Closer Body	Size 2 & 3 8-7/8"
	Size 4 & 5 9-3/4"
B. Horizontal Mounting Holes	Size 2 & 3 8-3-16"
	Size 4 & 5 9-1-16"
C. Vertical Mounting Holes	3/4"
D. Closer Body Height	1-31/32"
E. Projection from Door	2-29/32"



FRONT VIEW

END VIEW

PARTS AND ACCESSORIES

PRODUCT	DESCRIPTION	PART NUMBER
	Full Dress Cover	18-FDC
	Slim Dress Cover	18-SDC
	Complete Arm Assembly	18-CAA
	Cushion - Stop only arm	18-CSA
	Cushion - Hold-open arm - Mechanical Turn Type	18-CHM
	Friction Hold Open Arm	18-FHA
	Extended Long Rod	18-ELR
	Parallel Drop Plate	18-PDP
	Narrow Drop Plate	18-NDP
	Blade Stop Spacer	18-BSS
	Sex Nuts	18-SN

SPECIFY FINISH: AL - Aluminum
DU - Storefront Bronze

Visit our website: intldoorclosers.com



EAST:
1920 Air Lane Drive • Nashville, TN 37210
(615) 885-7060 • (800) 225-6737 • FAX: (615) 885-0903

WEST:
1140 North Kraemer Place • Anaheim, CA 92806
(714) 666-0390 • (800) 544-4422 • FAX: (714) 666-2215