

Finish

702	U	
-----	---	--

700 Series Finish

- 630 Dull stainless steel standard
- 605 Bright brass
- 606 Dull brass
- 613 Oil rubbed bronze
- 625 Bright Chrome

800 Series Finish

- AL 628 Anodized aluminum standard

Options

702	U	L2
-----	---	----

- ATS** Anit-Tamper switch
- L1** One LED; specify red or green
- L2** Two LED's; red and green
- LT** One tri-color LED; red green and amber
- RMB** Buzzer. May be wired to sound when door is unlocked. 12 or 24VDC operation with 700T only.
- SN** 85 db. siren, 3-28VDC with 700T only
- 10TD** Mini timer
- CYL-KD** Key cylinder with two keys

Dimensions

- 700** 2.875" x 4.5" x 20 Ga. (73 x 114 x 0.912mm)
- 700N** 1.75" x 4.5" x 20 Ga. (45 x 114 x 0.912mm)
- 700T** 4.5" x 4.5" x 20 Ga. (112 x 114 x 0.912mm)
- 800AL** 3.25" x 5" x .25"D (83 x 127 x 6.35mm)
- 800ALN** 1.75" x 5" x .25"D (45 x 127x 6.35mm)

10TD Mini Timer



The electronic Mini Timer provides timed unlocking and is compatible with all IDC momentary key and exit switches equipped with normally open contacts. The Mini Timer fits inside two gang key and exit switch assemblies, remote junction box and narrow frames.

- Voltage Input** 12/24VDC @ 50mA
- Trigger Input** N.O. dry
- Contact** SPDT dry, 2 Amps @ 30VDC
- Wire Leads** 7", 20 gauge
- Time Adjustment** 1 - 60 seconds
- Size** 0.75"W x 1.5"H .2.25"D
(19.05x 38.1 x 57.15mm)

Key Cylinder



- CYL-KD** 1.25" mortise key cylinder and 2 keys, keyed different, two different tail pieces provided. Dull chrome finish standard.