



Swinger 300

Pedestrian Gate Closer

Part 1 GENERAL

1.1 SECTION INCLUDES

- A. Swinger 300 – Pedestrian Gate Closer
- B. Features:
 - 1. Tough, dependable and Vandal resistant
 - 2. 2" x 4" x 12" (16 gauge) galvanized steel housing
 - 3. Gate closer manufactured for pedestrian gates
 - 4. Two separate Closing and Latching valves adjustable after installation without Removing the closer
 - 5. Non-handed (right or left swing)
 - 6. Opens to a full 105°
 - 7. Fully adjustable top arm for proper gate alignment
 - 8. Adjustable zinc plated Bottom Hinge with sealed ball bearings rated for 350 lbs.
 - 9. Designed to close gate into latch position without slamming
 - 10. Smooth operation
 - 11. Adjustable spring power to accommodate various gate sizes
 - 12. Factory tested to over 1,000,000 cycles

1.2 SUBMITTALS

- A. Product Data: Manufacturer's data sheets on each product to be used, including:
 - 1. Preparation instructions and recommendations
 - 2. Storage and handling requirements and recommendations
 - 3. Installation methods
- B. Shop Drawings: Manufacturer's approved drawings detail the application
- C. Section Samples: Samples are available depicting the finish types
- D. Verification Samples: For the finish product specified, two full size samples representing actual product, color and size

1.4 QUALITY ASSURANCE

Manufacturer Qualifications: The Swinger 300 will be provided by a single manufacturer with over 30 years of experience in door closers

1.5 DELIVERY, STORAGE AND HANDLING

- A. Store products in manufacturer's unopened packing until ready for installation
- B. No harsh chemicals are used during this process, so no special handling or disposal is required

1.6 PROJECT CONDITIONS

Maintain environmental conditions (temperature, humidity and ventilation) within limits recommended by the manufacturer for optimum results. Do not install this product if environmental conditions are outside the manufacturer's limits.

1.7 WARRANTY

After project completion, the owner or owner's representative will receive a copy of the Manufacturer's Limited Warranty against manufacturing defects.

Part 2 PRODUCTS

2.1 MANUFACTURER

International Door Closers Inc., (Manufacturer's Rep)

1140 North Kraemer Pl, Anaheim, CA 92806 - (800) 544-4422
1920 Air Lane Dr, Nashville, TN 37120 - (800) 225-6737

Part 3 EXECUTIONS

3.1 EXAMINATION

- A. Do not begin installation until substrates have been properly prepared
- B. If the substrate is the responsibility of another installer, notify the Architect of any unsatisfactory preparation before proceeding

3.2 PREPARATION

- A. Clean surfaces thoroughly prior to installation
- B. Prepare surfaces using the methods recommended by the manufacturer for achieving the best results for the substrate under the project conditions

3.3 INSTALLATION

- A. Install in accordance with manufacturer's instructions

3.4 PROTECTION

- A. Protect installed products until completion of project
- B. Repair or replace all damaged products before substantial completion

END OF SECTION