

LIMITED WARRANTY

INTERNATIONAL door closers purchased after January 1, 1995 are warranted by INTERNATIONAL Door Closers, Inc. to the original purchaser from the date of purchase in accordance with the following schedule.

OVERHEAD CONCEALED DOOR CLOSERS.....	5 Years
SURFACE MOUNTED DOOR CLOSERS (Commercial Type).....	5 Years

INTERNATIONAL door closers are warranted against any defects in workmanship and/or material only.

Products proven defective in the warranty period should be returned, postage or freight prepaid to:

INTERNATIONAL Door Closers, Inc., East: 1920 Air Lane Drive, Nashville, Tennessee 37210 or to

INTERNATIONAL Door Closers, Inc., West: 4431 E. La Palma Ave Anaheim, California 92807. They will be

replaced with brand-new (not rebuilt) closers at no charge with return postage or freight prepaid by

INTERNATIONAL Door Closers, Inc. No claims for damage incurred or work done thereon will be allowed.

This warranty is void if the products have been subjected to misapplication, abuse, or not installed in accordance with INTERNATIONAL's installation instructions.

Some states do not allow limitations on how long an implied warranty lasts. Some states do not allow the exclusion or limitation of incidental or consequential damage, so the above limitations may not apply to you. This warranty gives you specific legal rights. and you may also have other rights which vary from state to state.

RECOMMENDED DOOR CLOSER SIZE FOR TYPICAL DOORS

INTERIOR DOOR	EXTERIOR DOOR		TYPE	CLOSER SIZE
	Swing out	Swing in		
32" 28"	28" 24"	24" -	No Hold or Hold-Open parallel	1
36" 32"	32" 28"	28" 24"	No Hold or Hold-Open parallel	2
42" 36"	36" 32"	32" 28"	No Hold or Hold-Open parallel	3
48" 42"	42" 36"	36" 32"	No Hold or Hold-Open parallel	4
54" 48"	48" 42"	42" 36"	No Hold or Hold-Open parallel	5

NOTE: Doors of unusual height or weight, or doors subject to severe wind or draft condition or abusive usage, require the next larger model closer than the above schedule.

RECOMMENDED MAINTENANCE

All Door closers should be periodically inspected for the following.

1. All screws should be tightened securely.
2. There should not be any Hydraulic Fluid leaking.
3. Closers should be properly adjusted for correct speed of closing.
4. Doors should not be loose in the door jamb.

NOTE: Unscrewing the valve(s) all the way out will result in loss of door check fluid, causing the door to slam and voiding the warranty.